Sanitized Copy Approved for Release 2011/09/14: CIA-RDP80-00809A000600380105-3

CONFIDENTIAL CLASSIFICATION CONFIDENTIAL

CENTRAL INTELLIGENCE AGENCY

REPORT

50X1-HUM

L. INFORMATION FROM FOREIGN DOCUMENTS OR RADIO BROADCASTS

COUNTRY USSR

DATE OF

INFORMATION

1949

CD NO.

SUBJECT

Scientific -- Physics, silicon, semiconductors

HOW

Monthly periodical

PUBLISHED

WHERE

Moscow

PUBLISHED

DATE

Jan 1950

PUBLISHED LANGUAGE

Russian

NO. OF PAGES.. 2

DATE DIST. 24 Feb 1951

. 0.

SUPPLEMENT TO

REPORT NO.

THIS IS UNEVALUATED INFORMATION

SOURCE

Zhurnal Tekhnicheskov Fiziki, Vol XX, No 1, 1950, pp 3-26.

A SURVEY OF THE ELECTRICAL PROPERTIES OF SILICON

B. I. Boltaks Leningrad Phys-Tech Inst Acad Sci USSR Submitted 15 Sep 1949

Introduction

Recently, in connection with the use of silicon and its alloys in the preparations of many different types of detectors, semiconductor amplifiers, and photoresistances, great interest has been shown in the physical properties of, silicon, particularly its electrical properties. Information in the literature on the electrical properties of silicon is fragmentary and frequently contradictory. Therefore, it is thought expedient to outline here the basic data now known on silicon, mainly form the viewpoint of the modern theory of the mature of electrical properties in solids.

Mature of Electrical Conductivity in Silicon

. Gives historical discussion of Seeman, Wilson, Guden, Schulze's work on the dependence of silicon's specific resistance upon temperature.

Crystallic Structure of Silicon and Mature of Its Energy Zones

Considers the width of the forbidden zone:

 $r_{\mathbf{p}})|\mathbf{S}_{\mathbf{p}}|$

where e is the electron charge, Z the atomic number, so the atomic distance factor, n the totality of indexes of a given grain, d the lattice constant, and So the structural factor. Thus AW 2020 2.6 ev, according to foreign references.

Electrical Conductivity of Pure Silicon, and its Dependence on T

Considers the formulas:

 $\sigma = A_1 \cdot \exp(-B_1/T) + A_2 \cdot \exp(-B_2/T)$

where $B_1 = \Delta W_1/k$ and $B_2 = \Delta W_2/k$; and

CONFIDENTIAL CLASSIFICATION DISTRIBUTION HERB e i hayy

Sanitized Copy Approved for Release 2011/09/14: CIA-RDP80-00809A000600380105-3



50X1-HUM

O = noeu exp (-AN)/2007)

where \mathbf{a}_0 is the number of local levels of the admixture, and μ is the electrons's mobility in the conduction zone, as given in the literature.

Electrical Conductivity of Gertain Solid Solutions of Stlicon

Compares silicon solutions containing admixtures of boron, phosphorus, alminum, etc., relative to the concentration of charge carriers and quantity of admixture, as given by formey and Whitzer,

Measurements of Hall's Constant in Pure Silicon and in Silicon With Admixtures of Other Elements; Concentration of Charge Carriers and Their Mobility

Includes the data of Pearson, Bardsen, Torrey, Whitmer, and the author.

Thermoelectromotive Force of Silecon

Compares the following thermocomples: Si-Fb, Si-Bi, Si-Sb, Si-Te, Si-Se, Si-BiC, Si-Pt, Si-C, SiC-BC, Si-constantan, from the data of Week and Ellis.

Practical Use of Silicon in Semiconductor Techniques

Sonsiders thermo-enf versus T, and the spectral characteristics of photoresistors obtained by the pyrolytic deposition of silicon on porcelain.

- E # D -

CONFIDENTIAL

CONFIDENTIAL